

US-42876-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Name and address of the applicant

Name and address of the manufacturer

Name and address of the factory

Note: When more than one factory, please report on page 2

Ratings and principal characteristics

Trademark / Brand (if any)

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

Additional information (if necessary may also be reported on page 2)

A sample of the product was tested and found to be in conformity with

As shown in the Test Report Ref. No. which forms part of this Certificate

Hall Effect Current Sensors

ALLEGRO MICROSYSTEMS L L C 955 PERIMETER RD MANCHESTER, NH 03103-3353 UNITED STATES

ALLEGRO MICROSYSTEMS L L C 955 PERIMETER RD MANCHESTER, NH 03103-3353 **UNITED STATES**

ALLEGRO MICROSYSTEMS PHILIPPINES INC TEST CENTER SAMPAGUITA ST MARIMAR VILLAGE PARANAQUE, METRO MANILA, 1700 **PHILIPPINES**

☐ Additional Information on page 2

(Provided for reference only) □ Additional Information on page 2



ACS702ELC, ACS702LLC, ACS712ELC, ACS713ELC, ACS714ELC, ACS714LLC, ACS715ELC, ACS715LLC, ACS722LLC, ACS723LLC, ACS730LLC, ACS730KLC, ACS71240LLCB

□ Additional Information on page 2

Additionally evaluated to: EN 62368-1:2014, EN 62368-1:2014/A11:2017 National Differences: EU Group Differences, AU, CA, DK, FI, JP, NZ, NO, SE, GB, US

☐ Additional Information on page 2

IEC 62368-1:2014

E316429-A6006-CB-1 issued on 2023-10-24

This CB Test Certificate is issued by the National Certification Body



Date: 2023-10-24

■ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

1/2

□ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
□ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
□ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Signature:

Jolanta M. Wroblewska



US-42876-UL

Additional Model Detail(s):

ACS702ELC, ACS702LLC, ACS712ELC, ACS713ELC, ACS714ELC, ACS714LLC, ACS715ELC, ACS715LLC, ACS722LLC, ACS723LLC, ACS730LLC, ACS730KLC, ACS71240LLCB, Model numbers may be followed additional suffixes not affecting safety.

Additional Ratings:

(Provided for reference only)

Rated isolation voltage for Basic Insulation (Models ACS730LLC, ACS730KLC): 2400Vrms/3393Vpk (Tested to 2400Vrms for 1 minute) at Tma 150°C

Rated isolation voltage for Basic Insulation (All models except ACS730LLC, ACS730KLC): 1768Vrms/2500Vpk (Tested to 1768Vrms for 1 minute) at Tma 150°C 2400Vrms/3393Vpk (Tested to 2400Vrms for 1 minute) at Tma 125°C

Maximum Working Voltage for Basic Insulation (All models): 300Vrms or 425VDC / 425Vpk

Additional information (if necessary)



Date: 2023-10-24

■ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

□ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
□ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
□ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Signature:

Jolanta M. Wroblewska

Jolanda Pa, Will